

# SILENT AIR-COOLED RECIPROCATING AIR COMPRESSOR



## Features:

- ▶ Low noise, low vibrations operation.
- ▶ Simple operating with full automatic control.
- ▶ Compact design, small space requirements and easy installation.
- ▶ Adjustable feet enable installation even on the uneven foundation.
- ▶ Easy and convenient access for maintenance.
- ▶ Effective and efficient cooling system brings low outlet air temperatures and enables smooth long continuous operating.
- ▶ Pressure gauge and operation hour meter.



H-SERIES

LOW NOISE

LOW VIBRATIONS




# SILENT AIR-COOLED RECIPROCATING AIR COMPRESSOR



▲ H-10



▲ H-30



H系列



▲ H-50



▲ H-100

## Specifications:

Model	Motor HP/kw	Piston Displacement lit/min(CFM)	Working Pressure kg/cm <sup>2</sup> G	Air receiver volume(lit)		Control	Dimensions (mm)	External air-receiver volume(lit) (Optional)	Weight (kg)
				Internally installed	Buffer tank				
H-10	1(0.75)	185(6.5)	7	38	—	Automatic	800x590x990	—	132
H-30	3(2.2)	462(16.3)	7	13	—	Automatic	900x540x990	155	227
H-50	5(3.7)	767(27.1)	7	—	8	Automatic	860x705x1180	155	322
H-100	10(7.5)	1484(52.4)	7	—	8	Automatic/ Semi automatic	1050x930x1300	155	412

\*For other working pressures please contact manufacturer.

**FU SHENG INDUSTRIAL CO.,LTD.**

We reserve right to change specifications without prior notice.

HEADQUARTERS-No.172 Nanking E.Road, Sec.2, Taipei, Taiwan

TEL : (02)2507-2211 FAX : (02)2504-7870

SANCHUNGFACORY(SalesOffice)-No.60 Kwang Fu Road, Sec.2, Taipei County, Taiwan

TEL : (02)2995-1411 FAX : (02)2995-7925

WEBSITE:www.fusheng.com

E-MAIL:machinery@m.fusheng.com.tw